

## II. CLAIM AMENDMENTS

1. (Currently Amended) A method for positioning of a wireless communication device comprising:

storing position data of one or more reference points in at least one data base;

using the one or more reference points to predict a signal phase of a positioning system;

examining which of said one or more reference points is located in the vicinity of the wireless communication device;

transmitting at least position data about said reference point located in the vicinity of the wireless communication device to the wireless communication device; and

selecting the transmitted position data about said reference point located in the vicinity of the wireless communication device as the default position of the wireless communication device.

2. (Previously Presented) The method according to claim 1, further comprising:

using base stations of a mobile communication network as the one or more reference points;

defining a cell global identity for each base station; and

separating the one or more reference points according to cell global identity when storing the position data.

3. (Previously Presented) The method according to claim 2, further comprising establishing the at least one data base in the mobile communication network.

4. (Previously Presented) The method according to claim 2, further comprising:

setting up a communication connection between the wireless communication device and a certain one of the base stations of the mobile communication network; and

selecting the default position as a position of the certain one of the base stations.

5. (Previously Presented) The method according to claim 2, wherein the position data of the base stations is transmitted to the wireless communication device.

6. (Previously Presented) The method according to claim 2, further comprising:

setting up the at least one data base in a data base server; and

establishing a communication connection from the at least one data base to the wireless communication device to transfer the position data between the wireless communication device and the at least one data base.

7. (Previously Presented) The method according to claim 6, wherein a connection according to a WAP protocol is used as said communication connection.

8. (Previously Presented) The method according to claim 1, further comprising storing information on the position of the

one or more reference points in the wireless communication device.

9. (Previously Presented) The method according to claim 8, further comprising:

transmitting a cell global identity of a base station communicating with the wireless communication device to the wireless communication device;

determining whether any position data based on a cell global identity of a new base station are stored in the wireless communication device when the new base station communicates with the wireless communication device; and

sending a request from the wireless communication device for transmission of positioning data, to the wireless communication device when no position data based on the cell global identity of the new base station are stored in the wireless communication device.

10. (Previously Presented) The method according to claim 1, further comprising:

determining the position data of the one or more reference points at least in the wireless communication device;; and

transmitting the determined position data and an identity of an associated base station to be stored in the at least one data base.

11. (Currently Amended) A positioning system to be used in the positioning of a wireless communication device comprising:

at least one data base for storing one or more reference points;

a means for predicting a signal phase of a positioning system using the one or more reference points;

means for detecting which of said one or more reference points is located in the vicinity of the wireless communication device; and

means for transmitting position data of the reference point located in the vicinity of said wireless communication device to the wireless communication device, wherein the transmitted position data of said reference point in the vicinity of the wireless communication device is arranged to be selected as the default position of the wireless communication device.

12. (Previously Presented) The positioning system according to claim 11, wherein base stations of a mobile communication network are arranged to be used as the one or more reference points, a cell global identity is defined for each base station, and the one or more reference points are separated according to said cell global identity when storing position data of the one or more reference points.

13. (Previously Presented) The positioning system according to claim 12, wherein the at least one data base is established in the mobile communication network.

14. (Previously Presented) The positioning system according to claim 12, comprising means for establishing a communication connection between the wireless communication device and a certain one of the base stations of the mobile communication

network, wherein the selected default position is the position of that the certain one of the base stations.

15. (Previously Presented) The positioning system according to claim 12, comprising means for transmitting position data of the base stations of the mobile communication network to the wireless communication device.

16. (Previously Presented) The positioning system according to claim 12, wherein the at least one data base is set up in a data base server, and that the positioning system comprises means for setting up a communication connection from the at least one data base to the wireless communication device to transfer position data between the wireless communication device and the data base.

17. (Previously Presented) The positioning system according to claim 16, wherein a connection according to a WAP protocol is used as said communication connection.

18. (Previously Presented) The positioning system according to claim 11, wherein information on the position of the one or more reference points is stored in the wireless communication device.

19. (Previously Presented) The positioning system according to claim 18, comprising means for transmitting to the wireless communication device a cell global identity of a base station with which the wireless communication device is communicating;

the wireless communication device comprising means for determining whether position data based on a cell global identity of a new base station is stored in the wireless communication device when the new base station communicates with the wireless communication device, wherein a request to transmit

position data to the wireless communication device is arranged to be transmitted from the wireless communication device when no position data based on a cell global identity of the new base station is stored in the wireless communication device.

20. (Previously Presented) The positioning system according to claim 11, wherein the wireless communication device comprises:

means for determining position data for at least one of the one or more reference points; and

means for transmitting the determined position data and a cell global identity of a base station associated with the at least one of the one or more reference points,

wherein the positioning system comprises means for receiving and storing said determined position data and cell global identity into the data base.

21. (Currently Amended) An electronic device to be used in a positioning system comprising at least:

positioning means;

means for performing functions of a mobile communication device;

means for detecting which of a number of reference points stored in a data base of the positioning system is located in a vicinity of the electronic device;

means for using one or more of the number of reference points to predict a signal phase of a positioning system;

means for receiving position data of the reference point located in the vicinity of the wireless communication device; and

means for selecting the received position data of the reference point located in the vicinity of said wireless communication device as the default position of the wireless communication device.

22. (New) The method of claim 1, wherein the signal phase of the positioning system comprises one of:

a code phase;

a bit phase;

a subframe phase;

a frame phase; or

a Doppler shift.